

stop crime fast with the

RAPID DEPLOY

COMPACT | EFFECTIVE | VERSATILE | ECONOMICAL



Suitable for a wide range of applications

PIR motion sensor detection

Simple installation and arming

The Rapid Deploy fog generator has been designed and manufactured as a portable stand-alone system to protect spaces quickly and effectively. The Rapid Deploy uses the technology as our high-end security fog generators.

Our system is activated by a standard operating fob giving you complete control of the arm and disarming process, without needing to intergrate into an existing alarm system.

Set up and protection is a matter of minutes. All you need to install a Rapid Deploy security fog generator is a suitable plug socket, no engineer required. Each machine is fitted with a PIR to detect a human being moving around within approx 10m from the sensor.

This fog is very persistent and will stay suspended in the room for a significant length of time until it is vented by opening the doors and windows, keeping your property protected.



'ANTI-RAID' FIRST BURST

Turbo mode for maximum smoke generation in risk critical areas designed to stop thieves in their tracks.

VERSATILITY IS KEY

Compact and inexpensive, suitable for shops, server rooms, small offices, window displays and more.

MULTI-NOZZLE OPTIONS

A range of different nozzles are available to produce a range of different effects.

FEATURES

- 5-year warranty.
- Full heater redundancy protects against critical failure.
- 90 second initial burst for maximum smoke generation in risk critical areas.
- Compact and robust
- Energy save mode cuts costs in periods when the generator is not immediately needed.
- PIR detection included
- Extreme temperature operation: -10°C to 50°C.
- £10 million product and public liability insurance.
- Simple installation and arming

OPERATION

- 4 inputs and 7 outputs.
- LCD status display and on-board event log.

CONSTRUCTION

- Rugged and compact steel casing in white.
- Environmental pack for installation in confined spaces with elevated ambient temperatures.

STANDARDS COMPLIANCE

- EN50131:8 and IEC62642:8.
- CNPP Rating: Class I Category 30.

FLUID

- 1000ml Swift Fit bottle.

DATA

- 36.8(H) x 13.8(D) x 23.1(W) cm.
- Weight: 12 kg (pre-install), 14.5 kg (installed).

CAN'T SEE IT? CAN'T STEAL IT!